



“CHARLY” 200W LED HIGH BAY




Product Name	Charly			
SKU	K-10504	K-10505	K-10506	K-10507
CCT	3000K	4000K	5000K	5700K
LED Type	SAMSUNG 2835			
LED QTY	580PCS			
Luminous flux	170 Lm/W			
Luminous Flux	34000LM			
Beam Angle	120°			
CRI	>80Ra			
System Efficiency	>90			
Power Supply	LIFUD Dimmable 1-10V			
Input Voltage	AC 220-240V			
Power Frequency	50/60Hz			
Output Voltage	180-260VDC			
Output Current	0.5-0.75A(Constant Corrent)			
Power Efficiency	>90%			
Power Factor	>0.90			
Total Harmonic Distortion	<15%			
SystemPower consumption	200W±5W			
LED Power Consumption	190W±5W			
Fixture Material	ADC12 Aluminum alloy			
Ingress Protection	Ip65			
Net Weight	4.4kg ±0.3			
Grossweight	5.3kg ±0.5			
Lifespan	>50000Hrs(Ta=30°C @LM70)			
Junction Temperature	<75°C (Ta=30°C)			
Storage Temperature	(-40~ + 70°C)			
Operating Temperature	(-30~ + 50°C)			
Operating Humidity	15 - 90% RH			
Outlook Dimensions	Φ336*194mm			
Cartion size	L390*W390*H205mm			




200WSize




60° PC Reflector




90° PC Reflector



60° AL Reflector






90° AL Reflector






Installation method




Hoisting

1  Drilling a hole in the ceiling, install a hook.	2  Hanging the fixture.	3  Connect the cables. Black-L, White-N, Green-Ground take care of the waterproof processing.
--	---	---



Ceiling installation

1  Fix the bracket.	2  Connect the cables. Black-L, White-N, Green-Ground take care of the waterproof processing.	3  Adjust the bracket to the beam angle you need.
---	---	--



Wall mounting

1  Drilling holes in the ceiling, and install the expansion screws	2  walling installation	3 
--	---	---



glass/120
Asymmetrical Width
19,500 Lumens
5000K





90° AL Reflector
Asymmetrical Wide
19,500 Lumens
5000K



60° AL Reflector
Asymmetrical Ultra Wide
19,500 Lumens
5000K



90° PC Reflector
Asymmetrical Wide
19,500 Lumens
5000K



60° PC Reflector
Asymmetrical Ultra Wide
19,500 Lumens
5000K

